



# Cage-Weeder



With this machine KRESS & CO had given a total new idea to mechanical weed control. The absolutely new principle of effect and construction received the award for new inventions on the Agritechnica-Show. This new method of weed control and soil loosening works particularly very effective in early stadiums. The machine is good for all row crops particularly for vegetable, special crops, medicinal and spice plants, but also for field crops like sugar beets, sunflowers etc.



Two weeding cages in a row rotate in an adjustable depth of 1 - 4 cm in driving direction between the plant rows. The cage in front drives the rear one and also loosens the soil downwards. The second cage crumbles the soil and removes soil from the weed.




The ground driven machine is suitable for every standard tractor to mount in front, rear or between the axles. The modular concept allows quick mounting and adjusting to different working and row widths.



The total new tool construction causes no side pressure, therefore there is no need for row protection. Even seeded cultures can be hoed in very early stadium.

## K.U.L.T.-Cage Weeder

## Technical Data:



Attachment in front gives good sight to the plant-row, even at high speed



The Kress Cage-Weeder can be attached at every common Tool-Carrier



For larger working width, the maintenance-free chain-drive is mounted on both side.



The Kress Cage-Weeder can be also used for the whole space, to prepare seed- or plant-beds



Adjustable working-elements allow with easy handling, a quick and optimal adjustment to different working and row widths.

Objective of use:	early weeding without pushing the crust, with high efficiency
Range of use:	- vegetable gardening - tree nurseries - special cultures
Timing of use:	very early
Mode of operation:	the first tool bar (slowly) breaks the soil without pushing, the second tool bar (fast) loosens the soil and removes the weeds
Attachement:	in front, rear or between the axles, horse pulling
Row distance:	from 20 cm
Working width:	150 – 600 cm - up to 300 cm with rigid basic frame - from 300 to 600 cm there will be 2 / 3 extra mounted weeders (one per bed)
Clearance:	ca. 12 cm
Working depth:	2 - 4 cm
Working speed:	3 - 12 km/h
Ø of cage weeder elements:	35 cm
Width of standard cages:	14, 16, 18, 21, 24, 28, 33, 38 cm
Width of adjustable cages:	23-28 cm, 26-34 cm, 29-40 cm, 31-44 cm, 33-48 cm



K.U.L.T. Kress Umweltschonende Landtechnik GmbH  
Eberdinger Str. 37 · 71665 Vaihingen an der Enz  
Telefon +49(0)7042 37 665-0 · Telefax +49(0)7042 37 665-29  
info@kress-landtechnik.de · www.kress-landtechnik.de